

essentialShield Midi

Overview

The essentialShield Midi is a 10 Litre high-capacity sanitisation station, designed for large footfall and busy locations. It can process up to 25 users a minute, making it perfect for settings that require efficient hand sanitation quickly and effectively. Designed to stand neatly in shopping centres, airports, hospitals, nightclubs, sports stadiums, theme parks, school/colleges/universities, and conference centres where large volumes of people enter and move around freely.

essentialShield Range	2 years	3 years	4 years	5 years
Midi	£2.27	£1.52	£0.14	£0.90

Product Features

- Comes with a 10 Litre sanitiser solution tank capacity which dispenses over 52,500 doses before refill. We usually recommend each station comes with 10 Litres and 10 Litres in storage for refill.
- Processes up to 25 users a minute.
- Touch-free dispensing 'via' proximity sensor ensures maximum hygiene and safety.
- Unique 'top and bottom' touch-free twin jetting system that delivers 360-degree hand sanitiser coverage for optimum hygiene protection.
- Wide frontal and side panel surface's suitable for bespoke branding and logos.
- Calibration of solution quantity and dosing delivery amount can be adjusted 'via' smart phone to control multiple machine efficiency.
- Refill alert indicator to let you know when your station is low on solution before its runs out
- Anti-theft lockable sanitiser solution door, with key.
- Proximity sensor 'soft' dosing delivery which eliminates splashing and reduces wastage.
- Sleek aesthetically pleasing design with Zinc plated Iron steel casing. Ideal for larger footfall locations including entrance hallways, hotels, cruise ships, office blocks, public building and many more.
- Lifelong antimicrobial powder coating paint on all stations providing 99.99% protection against bacteria, viruses, biofilm and tested to ISO22196 standards.



All images are for visual representation only

Technical Features

Certifications	CE, EAC
Tank Capacity	10 litres
Canister Opening	32 mm
Dispense Rate	Adjustable dosing time from 0,2 to 2 seconds
Power Supply	100÷240 Vac @50/60 Hz
Electrical Class	Class I (ground connected)
Activation	Touch free via proximity sensor
Max Consumption	30 W
Operating Temperature	10-50°C
Storage Temperature	-20÷60°C
Case Material	Zinc plated Iron